

PROX SERIES

HID Proximity Readers



Benefits

- All Proximity Series Readers operate on low power for extended reader operation
- A LED indicator on the Prox Series readers visually confirms a successful read
- Prox Series readers are warranted for two years from date of shipment
- Prox Series readers are sealed in a rugged, weatherized polycarbonate enclosure to withstand harsh environments
- Prox Series readers use an advanced signal processing technique to communicate with proximity cards and key tags
- Prox Series readers are designed to provide protection against reader tampering



840 N. Third St, Suite 600
Milwaukee, WI 53203
Email: ati@atiaccess.com

Tel: (414) 289-3121
Fax: (414) 289-3129
Web Site: www.atiaccess.com

PROX SERIES

HID Proximity Readers

Specifications

PR-THIN-LINE

Dimensions 4.65" H x 2.95" W x 0.5" D (11.8 cm H x 7.5 cm W x 1.2 cm D)
Power Supply +5 to+16 VDC
Current 50 mA to 160 mA
Read Range 5.0" (12.70 cm) Typical

PR-MINI-PROX

Dimensions 6.0" H x 1.7" W x 1.0" D (15.2 cm H x 4.3 cm W x 2.54 cm D)
Power Supply +5 to+16 VDC
Current 50 mA to 160 mA
Read Range 5.0" (12.70 cm) Typical

PR-PROX-PRO

Dimensions 5.0" H x 5.0" W x 1.0" D (12.7 cm H x 12.7 cm W x 2.54 cm D)
Power Supply +10 to + 28.5 VDC
Current 100 mA to 160 mA peak
Read Range 8.0" (20.32 cm) Typical

PR-MAXI-PRO

Dimensions 12.0" H x 12.0" W x 1.0" D (30.5 cm H x 30.5 cm W x 2.54 cm D)
Power Supply +14 to +28.5 VDC
Current 1 to 1.7A peak
Read Range 24.0" (60.96 cm)

Typical

Colors Charcoal Grey
Operating Temperature..... -22° F to 150° F (-30° C to 65° C)

Ordering

PR-PROX-POINT-PLUS Reader 2 - 3" range
(5V) Charcoal Grey
PR-THIN-LINE Reader 4 - 5.5" range
(5V) Beige
PR-MINI-PROX Reader 4 - 5.5" range
(5V) Charcoal Grey
PR-PROX-PRO Reader 5.5 - 8" range
(12V) Charcoal Grey
PR-MAXI-PRO Reader 16 - 24" range
(24V) Charcoal Grey



840 N. Third St, Suite 600
Milwaukee, WI 53203
Email: ati@atiaccess.com

Tel: (414) 289-3121
Fax: (414) 289-3129
Web Site: www.atiaccess.com