

# MPS-S-1

## INSTALLATION INSTRUCTIONS

### EMERGENCY DOOR RELEASE



MPS-S-1

The MPS-S-1 "Break Glass" Emergency Door Release is ideal for immediate unlocking of perimeter doors or interior work area doors that are equipped with fail-safe electric locks. The MPS-S-1 with siren provides a local door alarm.

The MPS-S-1 is specifically designed for emergency door release and may influence the approval of an electric locking system.

This type of Emergency Door Release may be preferred over a pull station since greater commitment is required to break the glass.

## FEATURES

- Aluminum rod for striking the glass is included. (Not required to break the glass.)
- Blue painted finish with easy to read Activation Instructions avoids confusion with red Fire Alarm stations.
- Local door alarm siren included with MPS-S-1. Siren tone output at 24 VDC is: 95 db minimum @ 3 feet with glass plate removed. Siren operating voltage is: 3 to 28 VDC @ 30 mA maximum.
- DPDT 3 Amp Contacts - 1 SPDT for Lock Release and 1 SPDT Auxiliary contact for Remote Monitoring, CCTV Activation or Alarm Activation.
- The MPS-S-1 may initiate the release of an individual door or all doors connected to the Electric Locking System.
- The MPS-S-1 may be flush or recessed mounted in a 2" deep single gang box or double gang box with plaster ring cover.
- Two replacement glass plates included.

