



Benefits:

- **Advanced technology accuracy even with dirty, cut, scarred, aged, wet, and dry fingerprints**
- **Self contained unit stores over 4,000 fingerprints**
- **Flexible communication options including RS232, RS485 and Wiegand**
- **One touch enrollment**
- **Convenient VeriAdmin software package provides user-friendly fingerprint template enrollment and administration capabilities**
- **User-friendly installation with pigtail connections and single gang or mullion mount compatibility**
- **Intuitive user interface with red, green and amber LED signals**
- **Built-in Compatibility with most industry standard Wiegand formats, call for latest options**
- **VeriAdmin software for initial set-up, administration and networking functions**



VERY-FLEX-1

Very-Flex-1 Specifications:

Veriflex Dimensions	Length : 130 mm (5.12") Width : 50 mm (1.97") Depth : 56 mm (2.20')
Enrollment Time	<3 second
Identification Time	<1 second
Equal Error Rate (EER)	0.1%
Number of Templates	4000 per unit
Supply Current	Sleep: .15 amps @12V Identify/Verify: .30 amps @12V
Voltage	5 volts regulated, 6 to 24 volts unregulated

Mounting Specifications:

Flat Surface, Single Gang or Mullion Mountable Holes in wall mount plate will accept #6 screws or bolts. Clearance hole diameter is .155”.

Cutting-edge security and convenience:

Add biometric security to your installed readers in a snap! The Very-Flex-1 is the strong user authentication solution for forward thinking organizations that require heightened security for their existing access control systems. The Very-Flex-1 makes it possible to add the security of fingerprint verification to any reader that is capable of providing Wiegand communication in an industry standard format.

Ordering:

Options:

VERY-FLEX-1Add/Finger Reader